

VT Verso Housing

Protective housings for Axis network cameras



- > Indoor and outdoor
- > IP66 rating
- > IK10 rating
- > Side opening
- > Several mounting options

VT Verso Housings protect Axis network cameras in adverse conditions both outdoors and indoors. The stylishly designed, high quality housings offer IP66-rated protection against dust, heavy rain and UV rays.

Made of light-weight technopolymer the housings have high impact resistance. A side opening simplifies camera installation and maintenance.

VT Verso Housings enable the Axis network camera to operate in temperatures down to -20 °C (-4 °F).

Various brackets and accessories - such as ceiling and wall brackets, pole and corner mounts and adapters - are available.

VT Verso Housings are available separately or in kits with a variety of chosen Axis network cameras, mounts and other accessories.

Supported cameras are the indoor models of AXIS P13 and AXIS Q16 Series, and AXIS Q1755 Network Camera.



Technical Specifications – VT Verso Housing

| | |
|--------------------------|--|
| Models | VT Verso Housing VT Verso Cool Outdoor Housing |
| General | |
| Supported cameras | Indoor models of AXIS P13 and AXIS Q16, AXIS Q1755 |
| Casing | Color: White RAL 9002, Technopolymer (polycarbonate), 3 removable cable glands (2xPG9 & 1xPG11) IP66-rated and IK10 impact-resistant enclosure |
| Power | 230 V AC, 44 W |
| Environment | Indoor/outdoor |

| | |
|-----------------------------|---|
| Operating conditions | VT Verso Housing: -20°C to 40°C (-4°F to 104°F) VT Verso Cool Outdoor Housing: -20°C to 50°C (-4°F to 122°F) |
| Approvals | EN 60950-1, EN 50081-1, EN 50130-4, UL 94 V-1, EN 50102 IK10 VT Verso Housing: IEC/EN 60529 IP44 VT Verso Cool Outdoor Housing: IEC/EN 60529 IP66 |
| Weight | 1.5 kg (3.3 lb) including the sunshield |
| Included accessories | Sunshield, heater and thermostat and Installation Guide |
| Warranty | Axis 1-year warranty, see www.axis.com/warranty |

More information is available at www.axis.com

Optional accessories

1. Integrated junction box with adapter plate
2. Wall brackets
3. Ceiling brackets
- 4, 5, 6. Column brackets
7. Column bracket

Dimensions

422 mm (16.6 in)

466 mm (18.3 in)

142 mm (5.6 in)

156 mm (6.1 in)

Bracket accessories

1. Wall plate
2. Pole
3. Corner

Additional accessories

1. Power supply
2. Waterproof junction box